

AMENDMENTS TO THE CLAIMS

Please amend Claims 1, 3, 5, 9, 10, 13 and 14; and add new Claims 15 and 16 as follows.

LISTING OF CLAIMS

1. (currently amended) A heat exchanger having mounting members to which a blower is to be attached, comprising:

a plurality of metallic tubes through which fluid flows in a fluid flow direction;

a pair of metallic header tanks communicating with the plurality of tubes, each of the pair of header tanks being arranged at lengthwise opposite ends of the tubes and extending perpendicular to the lengthwise direction of the tubes, each of the pair of header tanks having defining a rectangular cross section defining fluid chamber having a long side wall surface and a short side wall surface, ~~said long wall side surface being longer than said short side wall surface~~, each of said header tanks being disposed such that said long side wall surface is generally parallel to said fluid flow direction and said short side wall surface is generally perpendicular to said fluid flow direction, concave and convex portions being formed in a first portion of the long side wall surface ~~of the rectangular cross section~~ of the header tank by plastic deformation;

a respective mounting member secured ~~[[to]]~~ on said long side wall surface ~~of the rectangular cross section~~ of each of the header tanks; and

a reinforcement attached to each of the mounting members on the side of the mounting member in contact with the long side wall surface, for strengthening the long side wall surface.

2. (cancelled)

3. (currently amended) A heat exchanger as defined by claim 1, wherein each of the reinforcements extends from a middle point of the long side wall surface toward opposite sides of the long side wall surface.

4. (cancelled)

5. (currently amended) A heat exchanger as defined by claim 1, wherein each of the reinforcements has a tapered section so that a cross-sectional area of the reinforcement increases as approaching the long side wall surface of the header tanks.

6. (cancelled)

7. (previously presented) A heat exchanger as defined in claim 1, wherein each of the reinforcements and a respective mounting member are integrally formed.

8. (cancelled)

9. (currently amended) A heat exchanger having mounting members to which a blower is to be attached, comprising:

a plurality of metallic tubes through which fluid flows in a fluid flow direction;

a pair of metallic header tanks communicating with the plurality of tubes, each of the pair of header tanks being arranged at lengthwise opposite ends of the tubes and extending perpendicular to the lengthwise direction of the tubes, each of the pair of header tanks ~~having~~ defining a rectangular cross section ~~defining~~ fluid chamber having a long side wall ~~surface~~ and a short side wall ~~surface~~, ~~said long wall side surface being longer than said short side wall surface~~, each of said header tanks being disposed such that said long side wall ~~surface~~ is generally parallel to said fluid flow direction and said short side wall ~~surface~~ is generally perpendicular to said fluid flow direction;

a respective mounting member secured ~~[[to]]~~ on said long side wall ~~surface of the rectangular cross section~~ of each of the header tanks; and

a reinforcement attached to each of the mounting members on the side of the mounting member in contact with the long side wall ~~surface~~, for strengthening the long side wall ~~surface~~, wherein the reinforcements and a respective mounting member are formed separately ~~[[form]]~~ from each other.

10. (currently amended) A heat exchanger as defined by claim 1, wherein each of the reinforcement and a respective mounting member are formed separately ~~[[form]]~~ from each other.

11. (previously presented) A heat exchanger as defined in claim 1, wherein the tubes are connected to each of the header tanks on the short side wall thereof.

12. (cancelled)

13. (currently amended) A heat exchanger having mounting members to which a blower is to be attached, the heat exchanger comprising:

a plurality of metal tubes through which fluid flows;

a pair of metallic header tanks communicating with the plurality of tubes;

each of the pair of header tanks defining a fluid chamber and being arranged at lengthwise opposite ends of the tubes and extending perpendicular to the lengthwise direction of the tubes, each of the fluid chambers defined by the pair of header tanks having a rectangular cross section in a direction parallel to the lengthwise direction of the tubes;

a respective mounting member secured to a longer side wall ~~surface of the rectangular cross section~~ of each of the header tanks, the mounting member being secured to a portion of the longer side wall ~~surface~~ forming the fluid chamber;

a reinforcement attached to each of the mounting members on the side of the mounting member in contact with the longer side wall ~~surface~~ for strengthening the longer side wall ~~surface~~ for strengthening the longer side wall ~~surface~~; and

concave and convex portions formed in a portion of the long side wall ~~surface of the rectangular cross section~~ of the header tank by plastic deformation.

14. (currently amended) A heat exchanger having mounting members to which a blower is to be attached, the heat exchanger comprising:

a plurality of metal tubes through which fluid flows;

a pair of metallic header tanks communicating with the plurality of tubes, each of the pair of header tanks being arranged at lengthwise opposite ends of the tubes and extending perpendicular to the lengthwise direction of the tubes, each pair of header tanks ~~having~~ defining a rectangular cross section fluid chamber in a direction parallel to the lengthwise direction of the tubes;

a respective mounting member secured to a longer side wall ~~surface of the rectangular cross-section~~ of each of the header tanks;

a reinforcement attached to each of the mounting member on the side of the mounting members in contact with the longer side wall ~~surface~~, the reinforcement defining an increased wall thickness in a localized area to strengthen the longer side wall ~~surface~~; and

concave and convex portions formed in a portion of the long side wall ~~surface of the rectangular cross-section~~ of the header tank by plastic deformation.

15. (new) A heat exchanger as defined by claim 1, wherein the respective mounting member is secured on a second portion of the long side wall, the second portion being different than the first portion.

16. (new) A heat exchanger as defined by claim 1, wherein each of the header tanks comprises a pair of L-shaped plate members in which said concave and convex portions are formed by press forming.